



Product Information Sheet: Asphalt Crack Filler 5L



Floorsaver Asphalt Crack Filler is a flexible rubberised bitumen formula, perfect for ensuring small cracks don't become large potholes.

- Mix and pour – no primer required
- Fast curing – dry in 2-4 hrs
- Use inside and out
- Suitable for asphalt and tarmac surfaces
- Flexible - Allows for movement/expansion
- Fills cracks 3mm to 25mm wide
- Can be painted over

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- Minimal preparation is required. floorsaver Asphalt Crack Filler is easy to use. Sweep or scrape out any loose stuff from the hole and that's about it.

Step 2 - Mixing:

- Still well before use
- Decant into a spouted can

Step 3 - Application:

In order to ensure proper drying time, please avoid using the product in wet or cold (below 5°C) conditions. Although some dampness may be tolerated, it is best for the crack to be reasonably dry.

Cracks up to 3mm wide: Using a spouted can (or watering can), apply the Asphalt Crack Filler to fill in the cracks, ensuring that any excess liquid that overflows is brushed out to create a thin film. Allow the filler to dry and then dust with fine sand or cement to remove any remaining tackiness.

Cracks 3mm - 25mm wide: Prepare the crack by applying a brush coat of floorsaver Asphalt Crack Filler to the sides. Create a slightly stiff mortar by mixing Asphalt Crack Filler with damp sand. Use a trowel to fill the crack and smooth it out. After the mortar dries, remove any remaining tack by dusting with fine sand or cement.

DRYING TIMES:

Approximately 2 - 4 hours should be allowed for cracks up to 3mm and 6 - 10 hours for cracks up to 25mm.

COVERAGE:

5 litres will fill 100 linear metres of cracks at 5mm wide & 5mm deep

SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

WE DON'T RECOMMEND:

This product is designed for use on bitumen based surfaces. It could soften surfaces which contain coal tar. If in doubt, apply a test area and check after 24 hours that no softening has occurred.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result. If you have any comments please email us at info@floorsaver.co.uk