



## Product Information Sheet: Floor Paint & Floor Paint Anti Slip 2.5L & 5L

Available in 190 RAL shades



### TOUGH, GLOSSY, POLYURETHANE FORMULA FOR CONCRETE FLOORS.

Floorsaver Floor Paint dustproofs, seals and protects internal concrete floors. Two coats provide a glossy, easily cleaned finish and the matt finish helps to disguise scratches and marks. It can be applied to bare concrete or existing well bonded paint. When recoating existing floor paint in a similar colour, one coat is generally all that is needed.

- Greatly improves the appearance of drab concrete
- Tough enough for warehouses, workshops and general use
- Single pack – just use as much as you need and replace the lid if you've got any left over
- Easy roller application
- Available in gloss or matt
- Choose Floor Paint Anti Slip for wet or slippery areas
- Resists spillages of oils and grease
- Suitable for concrete, wood and most metals
- 2.5L covers up to 20m<sup>2</sup> per coat
- 5L covers up to 40m<sup>2</sup> per coat

### HERE'S HOW TO USE IT:

#### Step 1 - Preparation:

- On bare, reasonably clean concrete wash with Floorsaver Floor Etcher. This cleans and keys the surface. On greasy or previously painted floors clean with Floorsaver Cleaner & Degreaser, scraping off any loose paint, dust or dirt. New concrete should be at least 2 months old and always washed with Floorsaver Floor Etcher to reduce alkalinity.

#### Step 2 - Repairs

- Fill holes using Floorsaver Pourable Concrete Filler.

#### Step 3 - Application:

- Check the floor is dry before painting and that the temperature is a minimum of 15°C.
- Stir the paint thoroughly.
- Do not thin.
- Tip into a roller tray.
- Cut in around edges with a brush.
- Apply to the floor area using a paint roller, working well into the surface. Bare concrete should be sufficiently porous to allow the first coat to sink in.
- If using Floorsaver Floor Paint Anti Slip, tip the small tin of Anti Slip Aggregate into the tin and stir thoroughly using a wooden batten or similar. Use the whole tin of aggregate for the 5L pack size and half for the 2.5L.
- Clean equipment with White Spirit.

### DRYING TIMES:

RECOAT	16 hours at 15°C - 20°C. The second coat should be applied within 5 days of the first coat.
TOUCH DRY	10 hours at 15°C - 20°C
LIGHT FOOT TRAFFIC	24 hours at 15°C - 20°C
FULL USE	36 hours at 15°C - 20°C. Please check that the paint has fully cured before putting into full use.

### WE DON'T RECOMMEND:

- Using this product in areas where cars are parked – instead use Floorsaver Epoxy Floor Paint.
- Using outside.
- Applying to self-levelling floor screeds.
- Applying to concrete contaminated with oil, grease, fats or wax.
- Applying to hard, smooth, very dense or power floated concrete where the paint can't soak into the surface. If in doubt tip a cup of water onto the floor and see if it disappears.

### SHELF LIFE:

3 years, if unopened and should not be allowed to freeze.

### SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

### ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments please email us at [info@floorsaver.co.uk](mailto:info@floorsaver.co.uk)