



Product Information Sheet: Multi-Purpose Paint 1L

Available in 190 RAL shades



AN ALL-IN-ONE PAINT SUITABLE FOR WOOD, METAL AND MORE.

Floorsaver Multi-Purpose Paint is designed for versatility and durability. Suitable for most surfaces with minimal preparation needed, this easy to use single pack paint offers lasting protection and an attractive gloss finish.

- For internal or external use
- Ideal for fences, pipework, gates, garden furniture, and outdoor metalwork
- Resistant against rain, sun, and temperature changes
- Single pack – use as needed, then reseal airtight and store at ambient temperature to use again.
- Easy roller or brush application
- Available in 190 RAL colours
- Goes on smoothly and dries quickly
- 10m² coverage per 1L per coat

HERE'S HOW TO USE IT:

Step 1 - Preparation:

Multi-Purpose Paint is self-priming. Multiple coats can be used if full coverage is not achieved in one coat.

Painted Surfaces – Using a wire brush or scraper, get rid of any peeling paint or loose rust. Check remaining paint is well bonded. Very smooth, glossy paint must be lightly abraded to provide a key.

Bare Metal - Any grease or oil should be removed with Floorsaver Cleaner & Degreaser or a similar degreasant. To improve adhesion, smooth metal surfaces can be prepared with a wire brush. All traces of degreasant should be washed away and the surface left completely clean, dry and free from loose material before painting.

Copper & Brass - If the surface has a green patina, this should be removed with phosphoric acid prior to painting.

Stainless Steel - Bristle blasting is recommended to provide a surface where the paint will adhere sufficiently.

Wood - Ensure the surface is clean and dry. Porous wood surfaces may require multiple coats to achieve desired finish.

Bare concrete - Wash with Floorsaver Floor Etcher, this cleans and keys the surface. On greasy or previously painted floors clean with Floorsaver Cleaner & Degreaser, scraping off any loose paint, dust or dirt. New concrete should be at least 2 months old and always washed with Floorsaver Floor Etcher to reduce alkalinity. Surfaces may require multiple coats to achieve desired finish.

Step 2 - Application:

- Check the surface is clean and dry before painting and that the temperature is a minimum of 15°C.
- Stir the paint thoroughly.
- Do not thin.
- Tip into a roller tray.
- Cut in around the edges with a brush.
- Apply to the area using a paint roller, working well into the surface.
- Clean equipment with White Spirit.

DRYING TIMES:

RECOAT 24 hours at 15°C - 20°C.

TOUCH DRY 8 hours at 15°C - 20°C

HARD DRY 24 hours at 15°C - 20°C

Please allow full hardness to develop before use.

Even after drying, it takes a few days to achieve optimal hardness and resistance. Avoid scratching, heavy loads, impacts, or cleaning chemicals during this time.

SHELF LIFE:

3 years, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve great results.

If you have any comments or need advice, please email us at info@floorsaver.co.uk