



## Product Information Sheet: Waterproof Roof Paint



### WATERPROOF AND PROTECT YOUR ROOF.

Floorsaver Waterproof Roof Paint is a bitumen based coating reinforced with rubber and fibre. This makes it flexible, unlike ordinary bitumen coatings, meaning it won't sag in the summer sun or split as the roof naturally flexes and moves. It can be used as an emergency leak stopper or to coat and extend the life of existing roofs.

- Thick and flexible roof coating which protects against the elements
- One coat, high build application
- Apply to roofing felt, asbestos type (porous) roofing sheets, corrugated iron, concrete and tiles
- Can be used on wet surfaces as an emergency repair
- Can be mixed with sand to fill holes, cracks and splits
- Easy brush or roller application
- Black finish gradually fades to grey
- Get a few more years out of your roof!
- Can be applied in temperatures as low as 5°C

### HERE'S HOW TO USE IT:

#### Step 1 - Preparation:

- Preparation is quite minimal. Sweep off any moss, algae or dirt. If there has been a heavy fungal infestation use a fungicide and wash off.
- You can use Floorsaver Waterproof Roof Paint in the rain as an emergency. For long term repairs the surface should be as dry as possible. When coating large areas, we recommend that they are dry as trapped moisture can delay drying.

#### Step 2 - Repairs:

- Holes, cracks and splits can be filled using Waterproof Roof Paint mixed with dry sand to form a stiff mortar. Prime the repair with a coat of Waterproof Roof Paint, then trowel in the mortar.

#### Step 3 - Application:

- No need to stir.
- Easiest using a brush, but a roller is possible on flat, felted surfaces or on flat concrete.
- Aim to use 1kg per 1m<sup>2</sup>.
- Clean equipment with White Spirit.
- Drying time approximately 24 hours.

### TIP:

- If there are 'suspect' areas of the roof such as panel overlaps or felt joints but you are intending to coat the whole roof, we recommend just running a brush line of Floorsaver Waterproof Roof Paint along the join, allowing it to dry and then coating the whole roof the following day.

### WE DON'T RECOMMEND:

- Applying Waterproof Roof Paint to bare timber to try to form a waterproof seal.
- Application to EPDM or similar rubber roof membranes, as the product can soften rubber. Test on a small area if in doubt about product suitability.
- Applying in exceptionally hot temperatures.

### SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

### SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

### ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result. If you have any comments please email us at [info@floorsaver.co.uk](mailto:info@floorsaver.co.uk)